

Insulated Roll Up Door

Model AM625: Insulated Heavy Duty Rolling Service Door



Keep the Heat Where it Belongs

If you need your rolling door to be energy efficient, the AM625 heavy duty Insulated Roll Up Door is right for the job. With its foamed-in-place polyurethane insulation and all around weatherseal, it keeps wind, water, and heat just where you want it. It also saves money on the energy bill.

Our AM625 Insulated Roll Up Door has many options. Choose from over 200 colors; aluminum, steel, or stainless steel slats; vision lites; numerous safety systems; and motorization as well.

- >> Thermal Protection with Foamed in Place Insulation
- >> Heavy Duty Construction
- >> ICC-ES Listed Air Infiltration Option
- >> High Wind Options
- >> Weathersealed Bottom Bar
- >> Chain Hoist, or Motorized

AmericanDoor.com
(631) 586-8006 (718) 895-6136

9 LUCON DR, DEER PARK, NY 11729

STANDARD FEATURES OVERVIEW

CONSTRUCTION

MAX HEIGHT	30' (9.14 meters)
MAX WIDTH	42' (12.8 meters)
MOUNTING	Face mount between jambs
OPERATION	Chain hoist. Optional Motorized (recommended)
MATERIAL	24 Gauge galvanized steel. Optional :18, 20, or 22 gauge, stainless steel, extruded aluminum.
THERMAL EFFICIENCY	7.7 R-Value .13 U-Value
INSULATION	Foamed-in-place polyurethane
SLAT PROFILE	Flat, insulated, sandwiched
CURTAIN	Alternating endlocks
WINDLOAD	20 PSF. (Optional 55 PSF for Florida and Dade County specifications)
SPRINGS	20k cycles standard
BOTTOM BAR	Double angle with weather seal and insulation.
LOCKING	Pad lockable on chain hoist, interlock on motorized
FINISH	Powder coated, galvanized, stainless, or aluminum


Other Options:

Air Infiltration Package (includes guide cover and cap, dual brush guide seal, lintel seal, bottom astragal); High Usage Setup; Vision Slats; Safety Systems; Sloping Bottom Bar; Pass Doors (Wicker Doors); Exhaust Ports, Drop Stop Device



Anatomy of an Insulated Slat:

Red: Front Slat
Blue: Back Slat
Orange: Foamed-in-Place insulation



Weatherseal:

Red: Seal attached to guide.
Blue: Guide
Black: Jamb Mounting



Bottom Bar with Weatherseal



AmericanDoor.com
(631) 586-8006 (718) 895-6136

9 LUCON DR, DEER PARK, NY 11729



Motor Mount Options:



Motor: Wall mounted motor
Slat: standard double-insulated flat slats.



Motor: L Plate mounted motor
Slat: Standard double-insulated flat slats plus vision slats.

Standard Powder Coat Options:



Some Safety and Security Systems Options for Motorized Doors:

Photo Eye

Detects people and vehicles passing the eye

Safety Edge

Detects the door closing on an object

Push Button Control

Station to control the door

Key Switch Control

Restricted access control

In-Ground Loop

Senses vehicles approaching

Radio Remote

Remotely operate the door

Horn

Alerts bystanders that door is in operation

Strobe Light

Alerts bystanders that door is in operation

and more...

We're happy to assist you with all of your security door needs. Just call



AmericanDoor.com
(631) 586-8006 (718) 895-6136

9 LUCON DR, DEER PARK, NY 11729

